





- Table standing luminaire for adjustable direct lighting
- Fully adjustable, articulated arm structures in extruded aluminum
- Joints and tension control knobs in polished die-cast aluminum
- Tension cables in stainless steel
- Base in weighted steel with stamped aluminum cover
- Internal tension springs and external tension control cables in stainless steel
- Tiltable and rotatable (360°) diffuser
- On/off switch on cord for Micro version
- On/off switch on head for Classic and Mini versions
- Base in weighted steel with stamped aluminum cover
- Tolomeo mini & classic black come with choice of aluminum or black base. Tolomeo micro black comes with black base
- Accessories available on pages 106 & 107
- **c.UL.us listed**




Tolomeo mini

finish

-  aluminum
-  white
-  black





light source

E26/A19
LED, CFL, INC - max 100W



Tolomeo classic

finish

-  aluminum
-  white
-  black
-  polished alum.

light source


E26/A19
LED, CFL, INC - max 100W

Tolomeo Clamp

- Made in die-cast aluminum
- Maximum thickness of table: 2" (5 cm)
- Minimum thickness of table: 1/2" (1,25 cm)


finish

■ aluminum



Tolomeo In-Set pivot

- Made in die-cast aluminum
- Maximum thickness of table: 2 1/2" (6,4 cm)
- Minimum thickness of table: 1/2" (1,25 cm)
- Maximum hole: ø 3/4" (1,9 cm)



finish

■ aluminum

