



# S29840

9.8A19/OMNI/220/LED/27K/GU24  
 9.8 watt; A19 LED; 2700K; GU24 base; 220' beam spread; 120 volts

### Features

- Solid State LED lighting
- A shaped replacement lamp
- Long life
- Approved for enclosed fixtures
- Dimmable



S29840

Item Number	UPC	Voltage	Watts	Incandescent Equivalent	Power Factor	Lamp Shape	Base
S29840	045923298400	120	9.8	60W	0.98	A19	GU24

  

Lamp Code	Dimmable/Non-Dimmable	Suggested Dimmers	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
9.8A19/OMNI/220/LED/27K/GU24	Dimmable	<a href="#">Compatible dimmers for S29840</a>	Frosted	4-3/16"	2-3/8"	800	25000

  

Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	ENERGY STAR
2700	Warm White	80	220	-25C (-13F) to a maximum of +45C (+113F)	24	Box	ENERGY STAR

  

CEC Status	RoHS Compliant	Fixture Type	UL or ETL Listed	UL Classification	Warranty
Non-Compliant <a href="#">Possible sub: S9707</a>	Yes	Enclosed Rated	Yes	cULus - Damp Location Rated	<a href="#">5 Year Limited - 10 hour use per day</a>



# S29819

15A19/LED/27K/1600/120V/GU24  
 15 watt; A19 LED; Frosted; 2700K; GU24 base; 220' beam spread; 120 volts

## Features

- Solid State LED lighting
- A shaped replacement lamp
- Long life
- Dimmable
- UL approved for totally enclosed fixtures



S29819

Item Number	UPC	Voltage	Watts	Incandescent Equivalent	Power Factor	Lamp Shape	Base
S29819	045923298196	120	15	100W	0.96	A19	GU24

Lamp Code	Dimmable/Non-Dimmable	Suggested Dimmers	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
15A19/LED/27K/1600/120V/GU24	Dimmable	<a href="#">Compatible dimmers for S29819</a>	Frosted	4-1/2"	2-3/8"	1600	25000

Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	ENERGY STAR
2700	Soft White	80	220	-25C (-13F) to a maximum of +45C (+113F)	24/6	Box	ENERGY STAR

CEC Status	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
Non-Compliant	Yes	Yes	cULus - Damp Location Rated	<a href="#">5 Year Limited - 10 hour use per day</a>